

S5200



Key Selling Points

- Captivating visualsntation
- Installation versatility
- Empowering usability
- Earth-caring functionality

StandardConfig

Display Technology	DLP™, Digital Light Display with ColorBoost II + and EcoProjection
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical colors	134 Million Colors
Brightness (ANSI lumens)	3,000 ANSI Lumens (Standard) 2,400 ANSI Lumens (ECO)
Dimension (WxDxH)	290 x 254 x 99 mm (11.4"x 10"x 3.9")
Weight	7.7 lbs (3.5Kg)
Contrast Ratio	2500:1
Noise Level	33 dBA (Standard mode) 28 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.6, f = 7.50mm, Manual Focus
Projection Screen	40"(102cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	161"@2m or 81"@1m (0.61:1)
Projection Distance	1.6'(0.5m) ~ 12.2'(3.7m)
Horizontal Scan	31.5-100KHz
Vertical Scan	56-120Hz
Lamp Type	Philips 210 W user replaceable UHP lamp
Lamp Life	4,000 Hours (ECO) 3,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual
Audio	Two Internal Speaker with 5 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	315 Watts (Operation) <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Input interface: Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 AV Audio (RCA L/R) x 1 Output interface: Analog RGB (D-sub) x 1 PC Audio (Stereo mini jack) x Control interface: RS232 (DE-9) x 1 Network interface: Ethernet port (RJ45) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT	
S5200 Brightness 3000, Lamp life 2000/3000, Native resolution XGA, Contrast ratio 2500:1, Throw ratio 161"@2m/81"@1m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 3.5, EAN 4717276014933	EY.K1405.001	EUR 749.00	

P5280



Target User

- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskisuuret yritykset
- Suuret yritykset

Key Selling Points

- High-impact projection
- Optimal usability
- Versatile multimedia
- Complete functionality

StandardConfig

Display Technology	DLP™, Digital light processor
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+(1,680x1,050)
Typical Colors	134 Million Colors
Brightness (ANSI lumens)	3,500 ANSI Lumens (Standard), 2,800 ANSI Lumens (ECO)
Contrast Ratio	2000:1
Noise Level	34 dBA (Standard mode), 31 dBA (ECO mode)
Weight	3.0Kg (6.6 lbs)
Dimensions	299 x 229 x 93 mm (11.8"x 9.0"x 3.7")
Digital Zoom	2x
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PIP)	N/A
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate:	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Projection Distance	3.3' (1.0m) ~ 39'(12.0m)
Projection Screen Size (Diagonal):	23" (0.58m) ~ 300" (7.62m)
Keystone Correction	+/-40 Degrees Vertical Keystone Correction
Audio	One Internal Speaker with 2 watts Output
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Lamp Type	260 W User Replaceable UHP Lamp
Power Consumption	355 Watts (Operation), 10 Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, DVI (HDCP) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord, VGA cable, Composite video cable, DVI cable, Remote control, Battery x 2 for remote control, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Ceiling Mounting Capability	Yes
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

model	part number	price + VAT	
P5280 Brightness 3500, Lamp light 2000/3000, Native resolution XGA, Contrast ratio 2000:1, Throw ratio 50"@2m, Zoom, Audio, HDMI, DVI, Warranty 2YR C&R, Weight 3.0, EAN 4712842106777	EY.J7501.001	EUR 699.00	

P5370W



Target User

- Kotikäyttäjät
- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskiuuret yritykset
- Suuret yritykset

Key Selling Points

- Spectacular display
- Confident usability
- Smooth connectivity
- Competent functionality

StandardConfig

Display Technology	DLP™, Digital light processor
Native Resolution	Native WXGA (1,280 x 800)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+(1,680x1,050)
Typical Colors	134 Million Colors
Brightness (ANSI lumens)	3,000 ANSI Lumens (Standard), 2,400 ANSI Lumens (ECO)
Contrast Ratio	2000:1
Noise Level	31 dBA (Standard mode), 28 dBA (ECO mode)
Weight	3.0Kg (6.6 lbs)
Dimensions	299 x 229 x 93 mm (11.8"x 9.0"x 3.7")
Digital Zoom	2x
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PIP)	N/A
Aspect Ratio	16:10 (Native), 4:3, 16:9
Horizontal Scan Rate:	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Projection Distance	3.3' (1.0m) ~ 32.9'(10.0m)
Projection Screen Size (Diagonal):	27" (0.69m) ~ 300" (7.62m)
Keystone Correction	+/-40 Degrees Vertical Keystone Correction
Audio	One Internal Speaker with 2 watts Output
Lamp Life	3,000 Hours (Standard), 4,000 Hours (ECO)
Lamp Type	220 W User Replaceable UHP Lamp
Power Consumption	300 Watts (Operation), 10 Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, DVI (HDCP) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1
Bundled Accesories	AC power cord, VGA cable, Composite video cable, DVI cable, Remote control, Battery x 2 for remote control, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Ceiling Mounting Capability	Yes
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

model	part number	price + VAT	
P5370W			
P5370W, DLP, ZOOM, XGA 1024x768, 3.0KG, '2000:1, 3000 LUMENS, Wide	EY.J6501.001	EUR 699.00	

P7270i



Target User

- Pienet ja keski suuret yritykset
- Suuret yritykset

Key Selling Points

- Splendid presentation
- Superior usability
- Multimedia pro
- Efficient functionality

Standard Config

Display Technology	DLP™, Digital light processor
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680x1050)
Typical Colors	1.07 Billion Colors
Brightness (ANSI lumens)	4,000 ANSI Lumens (Standard), 3,200 ANSI Lumens (ECO)
Contrast Ratio	2300:1
Noise Level	29 dBA (Standard mode), 27 dBA (ECO mode)
Weight	5Kg (11 lbs)
Dimensions	404 x 315 x 120 mm (15.9"x 12.4"x 4.7")
Wireless	Yes
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive), and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PIP)	Yes
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate:	27 ~ 92 kHz
Vertical Scan Rate	50 ~ 85 Hz
Projection Distance	3.9' (1.2m) ~ 32.0' (9.8m)
Projection Screen Size (Diagonal):	31" (0.78m) ~ 300" (7.62m)
Keystone Correction	+/-40 Degrees Vertical Keystone Correction
Audio	2 Internal Speakers each with 3 watts Output
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Lamp Type	280 W User Replaceable P-VIP Lamp
Power Consumption	TBD Watts (Operation), TBD Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1, Network Audio (Stereo mini jack) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1, Wired remote control port (Mini jack) x 1, 802.11b/g wireless technology, Ethernet port (RJ45) x 1, Wireless antenna connector (SMA) x 1
Bundled Accessories	AC power cord, VGA cable, Composite video cable, DVI cable, S-Video cable, Component cable, Remote control, Battery x 2 for remote control, Detachable antenna, Wireless PnS Token, Base of Wireless PnS Token, Detachable cable holder, Duster filter x 2, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Ceiling Mounting Capability	Yes
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

model	part number	price	+ VAT
P7270i Brightness 4000, Lamp life 2000/3000, Native resolution XGA Contrast ratio 2300:1, Throw ratio 63"@2m, Zoom, Audio, Wireless, HDMI, DVI, Warranty 2YR C&R, Weight 5,4, EAN 4712842106982	EY.J7701.001	EUR 799.00	

P7280



Target User

- Pienet ja keskisuuret yritykset
- Suuret yritykset

Key Selling Points

- Absorbing projection
- Versatile usability
- Complete connectivity
- Enhanced functionality

StandardConfig

Display Technology	DLP™, Digital light processor
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680x1,050)
Typical Colors	1.07 Billion Colors
Brightness (ANSI lumens)	4,500 ANSI Lumens (Standard), 3,600 ANSI Lumens (ECO)
Contrast Ratio	2300:1
Noise Level	34 dBA (Standard mode), 29 dBA (ECO mode)
Weight	5Kg (11 lbs)
Dimensions	404 x 315 x 120 mm (15.9"x 12.4"x 4.7")
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	Yes
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate:	27 ~ 92 kHz
Vertical Scan Rate	50 ~ 85 Hz
Projection Distance	3.9'(1.2m) ~ 32.0'(9.8m)
Projection Screen Size (Diagonal):	31"(78cm) ~ 300"(762cm)
Keystone Correction	+/-40 Degrees Vertical Keystone Correction
Audio	2 Internal Speakers each with 3 watts Output
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Lamp Type	330 W User Replaceable P-VIP Lamp
Power Consumption	TBD Watts (Operation), TBD Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2, Analog RGB (D-sub) x 1, PC Audio (Stereo mini jack) x 1, SPDIF Audio (RCA) x 1, USB (Type B) x 1, RS232 (Mini DIN) x 1, Wired remote control port (Mini jack) x 1
Bundled Accesories	AC power cord, VGA cable, Composite video cable, DVI cable, S-Video cable, Component cable, Remote control, Battery x 2 for remote control, Detachable cable holder, Duster filter x 2, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Ceiling Mounting Capability	Yes
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

model	part number	price + VAT	
P7280 Brightnes 4500, Lamp life 2000/3000, Native resloution XGA, Contrast ratio 2300:1, Throw ratio 63"@2m, Zoom, Audio, HDMI, DVI, Warranty 2YR C&R, Weight 5,4, EAN 4712842107064	EY.J7801.001	EUR 1199.00	

P5271i



Key Selling Points

- Enthralling visuals
- Installation flexibility
- Empowering usability
- Earth-caring functionality

StandardConfig

Display Technology	DLP™, Digital Light Display
Native Resolution	XGA 1024x768
Compressed Resolution	Maximum UXGA (1600 x 1200), 1080p (1920 x 1080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	3,100 ANSI Lumens (Standard) - 2,480 ANSI Lumens (ECO)
Dimension (WxDxH)	341 x 261 x 120 mm (13.4"x 10.3"x 4.7")
Weight	9.2 lbs (4.2 Kg)
Contrast Ratio	3700:1
Noise Level	26 dBA (ECO mode) - 29 dBA (Standard mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 3.2, f = 18.39mm ~ 29.42mm 1:1.6 Manual Zoom and Manual Focus
Projection Screen	28"(71cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	61"@2m (1.62 ~ 2.64:1)
Projection Distance	4.9'(1.5m) ~ 32.4'(9.9m)
Horizontal Scan	30k ~ 100k Hz
Vertical Scan	50-85Hz, 50 ~ 120 Hz (Available from Dec 2009)
Lamp Type	Osram 230 W user replaceable P-VIP lamp
Lamp Life	4'000 Hours (ECO) - 2'500 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	295 Watts (Operation), <1 Watts (Standby, wireless off)
Uniformity	90%
I/O Connectors	Input Interface: Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 DVI (HDCP) x 1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 2 USB (Type B) x 1 RS232 (Mini DIN) x 1 Output Interface: Analog RGB (D-sub) x 1 Network Audio (Stereo mini jack) x 1 Control Interface: USB (Type B) x 1 RS232 (Mini DIN) x 1 Wired remote control port (Mini jack) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable DVI cable Remote control Battery x 2 for remote control Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT	
P5271i Brightness 3100, Lamp light 2500/4000, Native resolution XGA, Contrast ratio 3700:1, Throw ratio 61"@2m, Zoom, Audio, Wireless, HDMI, DVI, Warranty 2YR C&R, Weight 4,2, EAN 4712842453345	EY.J8701.012	EUR 799.00	

P5271

**Target User**

- Kotikäyttäjät
- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskisuuret yritykset
- Suuret yritykset

Key Selling Points

- Remarkable display
- Installation flexibility
- Empowering usability
- Eco-friendly functionality

StandardConfig

Display Technology	DLP™, Digital Light Display
Native Resolution	XGA 1024x768
Compressed Resolution	Maximum UXGA (1600 x 1200), 1080p (1920 x 1080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	3'100 ANSI Lumens (Standard) - 2'480 ANSI Lumens (ECO)
Dimension (WxDxH)	341 x 261 x 120 mm (13.4"x 10.3"x 4.7")
Weight	8.9 lbs (4.1 Kg)
Contrast Ratio	3700:1
Noise Level	26 dBA (ECO mode) - 29 dBA (Standard mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 3.2, f = 18.39mm ~ 29.42mm 1:1.6 Manual Zoom and Manual Focus
Projection Screen	28"(71cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	61"@2m (1.62 ~ 2.64:1)
Projection Distance	4.9'(1.5m) ~ 32.4'(9.9m)
Horizontal Scan	30k ~ 100k Hz
Vertical Scan	50-85Hz, 50 ~ 120 Hz (Available from Dec 2009)
Lamp Type	Osram 230 W user replaceable P-VIP lamp
Lamp Life	4'000 Hours (ECO) - 2'500 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	290 Watts (Operation), <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Input Interface: Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 DVI (HDCP) x 1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 2 USB (Type B) x 1 RS232 (Mini DIN) x 1 Output Interface: Analog RGB (D-sub) x 1 Control Interface: USB (Type B) x 1 RS232 (Mini DIN) x 1 Wired remote control port (Mini jack) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable DVI cable Remote control Battery x 2 for remote control Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty and 1 year for the lamp.

model	part number	price	+ VAT
P5271 Brightness 3100, Lamp light 2500/4000, Native resolution XGA, Contrast ratio 3700:1, Throw ratio 61"@2m, Zoom, Audio, HDMI, DVI, Warranty 2YR C&R, Weight 4,1, EAN 4712842453253	EY.J8701.001	EUR 669.00	

P5290



Key Selling Points

- Remarkable display
- Installation flexibility
- Empowering usability
- Eco-friendly functionality

StandardConfig

Display Technology	DLP™, Digital Light Display
Native Resolution	XGA 1024x768
Compressed Resolution	Maximum UXGA (1600 x 1200), 1080p (1920 x 1080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	4000 ANSI Lumens (Standard) - 3200 ANSI Lumens (ECO)
Dimension (WxDxH)	341 x 261 x 120 mm (13.4"x 10.3"x 4.7")
Weight	8.9 lbs (4.1 Kg)
Contrast Ratio	3700:1
Noise Level	30 dBA (ECO mode) - 33 dBA (Standard mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 3.2, f = 18.39mm ~ 29.42mm 1:1.6 Manual Zoom and Manual Focus
Projection Screen	28"(71cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	61" @ 2m (1.62 ~ 2.64:1)
Projection Distance	4.9'(1.5m) ~ 32.4'(9.9m)
Horizontal Scan	30k ~ 100k Hz
Vertical Scan	50 ~ 120 Hz
Lamp Type	Osram 280 W user replaceable P-VIP lamp
Lamp Life	3000 Hours (ECO) - 2000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	345 Watts (Operation), <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Input Interface: Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 DVI (HDCP) x 1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 2 USB (Type B) x 1 RS232 (Mini DIN) x 1 Output Interface: Analog RGB (D-sub) x 1 Control Interface: USB (Type B) x 1 RS232 (Mini DIN) x 1 Wired remote control port (Mini jack) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable DVI cable Remote control Battery x 2 for remote control Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT
P5290		
P5290 XGA, 4.1Kg, 3700:1, 4000Lm, ECO, CBII+, Zoom, Bag, EUR/UK/SWI EMEA	EY.J9301.001	EUR 799.00

P5205

**Key Selling Points**

- Captivating visuals
- Installation versatility
- Empowering usability
- Earth-caring functionality

StandardConfig

Display Technology	DLP™, Digital Light Display
Native Resolution	XGA 1024x768
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical colors	134 Million Colors
Brightness (ANSI lumens)	4,000 ANSI Lumens (Standard), 3,200 ANSI Lumens (ECO)
Dimension (WxDxH)	290 x 254 x 99 mm (11.4"x 10"x 3.9")
Weight	7.2 lbs (3.3Kg)
Contrast Ratio	2500:1
Noise Level	34 dBA (Standard mode), 29 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native, 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.59 ~ 2.87, f = 16.88mm ~ 21.88mm, 1:1.3 Manual Zoom and Manual Focus
Projection Screen	30"(76cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	65"@2m (1.51 ~ 1.97:1)
Projection Distance	3.9'(1.2m) ~ 30.2'(9.2m)
Horizontal Scan	31.5 ~ 100 kHz
Vertical Scan	56 ~ 120 Hz
Lamp Type	Philips 280 W user replaceable UHP lamp
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical), Manual
Audio	Two Internal Speaker with 5 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	425 Watts (Operation), <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Input Interface: Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 AV Audio (RCA L/R) x 1 Output Interface: Analog RGB (D-sub) x 1 PC Audio (Stereo mini jack) x 1 Control Interface: RS232 (Mini DIN) x 1 12V DC (Screen control) x 1 Network Interface: Ethernet port (RJ45)
Bundled Accessories	AC power cord VGA cable Composite video cable Remote control Battery x 2 for remote control Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT
P5205 Brightness 4000, Lamp life 2000/3000, Native resolution XGA, Contrast ratio 2500:1, Throw ratio 65"@2m, Zoom, Wireless, HDMI, Warranty 2YR C&R, Weight 3,3, EAN 4717276014841	EY.K1305.001	EUR 749.00

S1200 - Ultra-short throw



Target User

- Kotikäyttäjät
- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskisuuret yritykset
- Suuret yritykset

Key Selling Points

- Impressive, sophisticated presentation
- Environmentally friendly projection
- Empowering usability, prolific connectivity
- Enhanced functionality

StandardConfig

Display Technology	DLP™, Digital Light Display with ColorBoost II and EcoProjection
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical colors	134 Million Colors
Brightness (ANSI lumens)	2,500 ANSI Lumens (Standard) 2,000 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 275 x 103 mm (10.6"x 10.8"x 4.1")
Weight	6.6 lbs (3.0 Kg)
Contrast Ratio	2000:1
Noise Level	32 dBA (Standard mode) 28 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.6, f = 6.97mm, Manual Focus
Projection Screen	41"(104cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	164"@2m or 82"@1m (0.60:1)
Projection Distance	1.6'(0.5m) ~ 12.0'(3.7m)
Horizontal Scan	31.5-100KHz
Vertical Scan	56-85Hz
Lamp Type	200 W user replaceable P-VIP lamp
Lamp Life	4,000 Hours (ECO) 3,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical)
Audio	One Internal Speaker with 8 watts Output
Power Supply	AC input 100-240V auto-switching power supply
Power Consumption	275 Watts (Operation) <5 Watts (Standby)
Uniformity	90%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 Analog RGB (D-sub) x 1 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty and 90 days for the lamp.

model	part number	price + VAT
S1200 Brightness 2500, Lamp life 3000/4000, Native resolution XGA, Contrast ratio 2500:1, Throw ratio 164"@2m/82"@1m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 3,0, EAN 4712842083061	EY.J8001.001	EUR 699.00

P7290

**Key Selling Points**

- Exceptional display
- Versatile installation
- Empowering usability
- Earth-friendly functionality

StandardConfig

Display Technology	DLP™, Digital light processor
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680x1,050)
Typical Colors	1.07 Billion Colors
Brightness (ANSI lumens)	5,000 ANSI Lumens (Standard), 4,000 ANSI Lumens (ECO)
Contrast Ratio	3000:1
Noise Level	35 dBA (Standard mode), 29 dBA (ECO mode)- w/o dust filter
Weight	5.4Kg (12 lbs)
Dimensions	404 x 315 x 120 mm (15.9"x 12.4"x 4.7")
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Picture in Picture (PiP)	Yes
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate:	27 ~ 92 kHz
Vertical Scan Rate	50 ~ 85 Hz
Projection Distance	3.9'(1.2m) ~ 31.4'(9.6m)
Projection Screen Size (Diagonal):	31"(79cm) ~ 300"(762cm)
Keystone Correction	+/-40 Degrees (Vertical), +/-15 Degrees (Horizontal), Manual
Audio	Two Internal Speaker with 3 watts Output
Lamp Life	2,000 Hours (Standard), 3,000 Hours (ECO)
Lamp Type	Philips 350 W user replaceable P-VIP lamp
Power Consumption	460 Watts (Operation), 1 Watts (Standby)
I/O connectors	Analog RGB/Component Video (D-sub) x 2, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, Audio, HDCP) x 1, DVI (HDCP) x 1, PC Audio (Stereo mini jack) x 2, Output interface: Analog RGB (D-sub) x 1, SPDIF Audio (RCA) x 1, Control interface: USB (Type B) x 1 RS232 (Mini DIN) x 1 Wired remote control port (Mini jack) x 1
Bundled Accessories	AC power cord, VGA cable, Composite video cable, DVI cable, S-Video cable, Component cable, Remote control, Battery x 2 for remote control, Detachable cable holder, Duster filter x 2, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Ceiling Mounting Capability	Yes
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT
P7290 Brightness 5000, Lamp life 2000/3000, Native resolution XGA, Contrast ratio 3000:1, Throw ratio 63"@2m, Zoom, Audio, HDMI, DVI, Warranty 2YR C&R, Weight 5.4, EAN 4717276011840	EY.K0801.001	EUR 1599.00

P1206

**Key Selling Points**

- Prolific imagery
- Convenient installation
- Empowering usability
- Eco-friendly functionality

StandardConfig

Display Technology	DLP®
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200) 1080p (1,920 x 1,080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	3700 ANSI Lumens (Standard) 2800 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 206 x 84 mm (10.6"x 8.1"x 3.3")
Weight	5.6 lbs (2.52 Kg)
Contrast Ratio	3700:1
Noise Level	34 dBA (Standard mode) 31 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen	23"(58cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Horizontal Scan	30-100KHz
Vertical Scan	50-120Hz
Lamp Type	Osram 230 W user replaceable P-VIP lamp
Lamp Life	4000 Hours (ECO) 2500 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	290 Watts (Operation) <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Input Interface Analog RGB/Component Video (D-sub) x 2 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, Audio, HDCP) x 1 PC Audio (Stereo mini jack) x 2 Output Interface Analog RGB (D-sub) x 1 PC Audio (Stereo mini jack) x 2 Control Interface USB (Type B) x 1 RS232 (Mini DIN) x 1 12V DC (Screen control) x 1 12V DC (Screen control) x 1
Bundled Accessories	AC power cord VGA cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT
P1206 Brightness 3600, Lamp life 2500/4000, Native resolution XGA, Contrast ratio 3700:1, Throw ratio 50"@2m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 2,5, EAN 4717276017804	EY.K1801.001	EUR 639.00

P1203



Key Selling Points

- Prolific imagery
- Convenient installation
- Empowering usability
- Eco-friendly functionality

StandardConfig

Display Technology	DLP®
Native Resolution	Native XGA (1024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200) 1080p (1,920 x 1,080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	3100 ANSI Lumens (Standard) 2480 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 206 x 84 mm (10.6"x 8.1"x 3.3")
Weight	5.5 lbs (2.48 Kg)
Contrast Ratio	3700:1
Noise Level	34 dBA (Standard mode) 31 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WUXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen	23"(58cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Horizontal Scan	30-100KHz
Vertical Scan	50-120Hz
Lamp Type	Osram 230 W user replaceable P-VIP lamp
Lamp Life	4000 Hours (ECO) 2500 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	290 Watts (Operation) <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Input: Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 Output: Analog RGB (D-sub) x 1 PC Audio (Stereo mini jack) x 1 Control Interface: USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord VGA cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT	
P1203 Brightness 3100, Lamp life 2500/4000, Native resolution XGA, Contrast ratio 3700:1, Throw ratio 50"@2m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 2,5, EAN 4717276017026	EY.K1701.001	EUR 569.00	

P1200



Target User

- Kotikäyttäjät
- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskisuuret yritykset

Key Selling Points

- Prolific imagery
- Convenient installation
- Empowering usability
- Eco-friendly functionality

Standard Config

Display Technology	DLP™, Digital Light Display with Colorboost II+ and EcoProjection
Native Resolution	Native XGA (1024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200) 1080p (1,920 x 1,080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	2,600 ANSI Lumens (Standard) 2,080 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 206 x 84mm (10.6"x 8.1"x 3.3")
Weight	5.2 lbs (2.34 Kg)
Contrast Ratio	3700:1
Noise Level	28 dBA (Standard mode) 25 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen	23"(58cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Horizontal Scan	30k ~ 100k Hz
Vertical Scan	50-120Hz
Lamp Type	Osram 180 W user replaceable P-VIP lamp
Lamp Life	5,000 Hours (ECO) 4,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	255 Watts (Operation) <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 Analog RGB (D-sub) x 1 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord VGA cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT
P1200 Brightness 2600, Lamp life 3000/4000, Native resolution XGA, Contrast resolution 4000:1, Throw ratio 50"@2m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 2,5, EAN 4717276017576, Nvidia 3D	EY.K1601.001	EUR 549.00

P1100

**Key Selling Points**

- Captivating visuals
- Installation versatility
- Empowering usability
- Earth-caring functionality

StandardConfig

Display Technology	DLP®
Native Resolution	Native SVGA (800 x 600)
Compressed Resolution	Maximum UXGA (1,600 x 1,200) 1080p (1,920 x 1,080)
Typical colors	1.07 Billion Colors
Brightness (ANSI lumens)	2,600 ANSI Lumens (Standard) 2,080 ANSI Lumens (ECO)
Dimension (WxDxH)	269 x 206 x 84 mm (10.6"x 8.1"x 3.3")
Weight	5.2 lbs (2.34 Kg)
Contrast Ratio	4000:1
Noise Level	28 dBA (Standard mode) 25 dBA (ECO mode)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 Native 16:9 compatible
Picture in Picture Support	N/A
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm 1:1.1 Manual Zoom and Manual Focus
Projection Screen	23"(58cm) ~ 300"(762cm)
Digital Zoom	2X
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Horizontal Scan	30-100KHz
Vertical Scan	50-120Hz
Lamp Type	Osram 180 W user replaceable P-VIP lamp
Lamp Life	5,000 Hours (ECO) 4,000 Hours (Standard)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Audio	One Internal Speaker with 2 watts Output
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	235 Watts (Operation) <1 Watts (Standby)
Uniformity	90%
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 Analog RGB (D-sub) x 1 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories	AC power cord VGA cable Remote control Battery x 2 for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	All of Acer projectors support a two year carry-in warranty, five years warranty for the DMD chip and one year warranty for the lamp.

model	part number	price + VAT
P1100 Brightness 2600, Lamp life 3000/4000, Native resolution SVGA, Contrast ratio 4000:1, Throw ratio 50"@2m, Zoom, Audio, HDMI, Warrenty 2YR C&R, Weight 2,5, EAN 4717276017453	EY.K1501.001	EUR 429.00

K10

**Target User**

- Kotikäyttäjät
- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keski suuret yritykset
- Suuret yritykset

Key Selling Points

- Radiant display, light weight
- Convenient, mobile usability
- Enduring, efficient functionality

StandardConfig

Display Technology	DLP™, Digital Light Processor with LED illumination
Native Resolution	Native SVGA (858 x 600)
Compressed Resolution	Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)
Typical Colors	16.7 Million Colors
Audio	No
Brightness (ANSI lumens)	100 ANSI Lumens
Contrast Ratio	2'000:1
Throw Ratio	50"@2m (1.97:1)
Noise Level	28 dBA
Weight	0.55 Kg (1.21 lbs)
Dimensions	127 x 122 x 48.5 mm
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
IR Remote Control	No
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate	31k ~ 69k Hz
Vertical Scan Rate	56 ~ 85 Hz
Projection mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Distance	2.0'(0.6m) ~ 7.9'(2.4m)
Projection Screen Size (Diagonal)	15"(38cm) ~ 60"(152cm)
Digital Zoom	No
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Lamp Life	LED life 20,000 Hours
Lamp Type	LED
Ceiling Mounting Capability	Not available
Power Consumption	55 Watts (Operation), <1 Watts (Standby)
Power Supply	DC input 19V via a 90W power adapter (AC input 100~240V auto-switching to DC 19V)
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Carrying case User's guide (CD-ROM) Quick start guide
Warranty	Acer projectors support a 2 year carry-in warranty and 90 days warranty for the lamp.

model	part number	price + VAT
K10 Brightness 100, Lamp life 20 000, Native resolution SVGA, Contrast ratio 2000:1, Throw ratio 50"@2m, Warranty 2YR C&R, Weight 0,5, EAN 4712842336952, Pico	EY.J8604.001	EUR 339.00

P3250



Target User

- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskisuuret yritykset
- Suuret yritykset

Key Selling Points

- kompakti kuvanheijastus
- runsaat käyttömahdollisuudet
- Luotettava liitettävyys
- Tehokas toimivuus

StandardConfig

Display Technology	DLP™, Digital Light Processor
Native Resolution	Native XGA (1,024 x 768)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Typical Colors	134 Million Colors
Audio	One Internal Speaker with 1 watts Output
Brightness (ANSI lumens)	2,000 ANSI Lumens (Standard), 1,500 ANSI Lumens (ECO)
Contrast Ratio	2000:1
Throw Ratio	50" @ 2m (1.95 ~ 2.15:1)
Noise Level	36 dBA (Standard mode), 29 dBA (ECO mode)
Weight	2.7 lbs (1.2 Kg)
Dimensions	210 x 165 x 64 mm (8.3"x 6.5"x 2.5")
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Horizontal Scan Rate	31.5 ~ 100 kHz
Vertical Scan Rate	56 ~ 85 Hz
Projection mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Projection Distance	3.3'(1.0m) ~ 39.0'(11.9m)
Projection Screen Size (Diagonal)	23"(58cm) ~ 300"(762cm)
Digital Zoom	Yes, 2x
Keystone Correction	+/-40 Degrees (Vertical)
Lamp Life	3,000 Hours (Standard), 5,000 Hours (ECO)
Lamp Type	Osram 165 W user replaceable P-VIP lamp
Ceiling Mounting Capability	Not available
Power Consumption	235 Watts (Operation), <5 Watts (Standby)
Power Supply	AC input 100~240V auto-switching power supply
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x1 HDMI (Video, HDCP) x 1 PC Audio (Stereo mini jack) x 1 USB (Type B) x 1
Bundled Accessories	AC power cord VGA cable Composite video cable Remote control Battery for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	Acer projectors support a 2 year carry-in warranty and 90 days warranty for the lamp.

model	part number	price + VAT	
P3250 Brightness 2000, Lamp life 3000/5000, Native resolution XGA, Contrast ratio 2000:1, Throw ratio 50" @ 2m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 1,2, EAN 4712842156321	EY.J8501.001	EUR 669.00	

H7530D

Target User

- Kotikäyttäjät

Key Selling Points

- Immersive display
- Keeping images alive
- One-click functionality
- In full control

StandardConfig

Display Technology	DLP™ Digital Light Processor
Native Resolution	Native 1080p (1,920 x 1,080)
Compressed Resolution	Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Typical Colors	1.07 Billion Colors
Brightness (ANSI lumens)	2,000 ANSI Lumens (Standard), 1,600 ANSI Lumens (ECO)
Contrast Ratio	40000:1
Throw Ratio	60" @ 2m
Noise Level	30 dBA (Standard mode), 26 dBA (ECO mode)
Weight	3.2 kg (6.9 lbs)
Dimensions	294 x 229 x 95 mm (11.6"x 9.0"x 3.7")
Computer Compatibility:	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
IR Remote Control	included
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio:	16:9 (Native), 4:3 Compatible
Horizontal Scan Rate:	30 ~ 100 kHz
Projection mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Vertical Scan Rate:	50 ~ 85 Hz
Projection Distance:	4.9'(1.5m) ~ 32.9'(10.0m)
Projection Screen Size (Diagonal):	37"(94cm) ~ 300"(762cm)
Digital Zoom	Yes, 8X
Keystone Correction:	+/-15 Degrees (Vertical), Manual and Auto
Lamp Life	2,500 Hours (Standard), 4,000 Hours (ECO)
Lamp Type	230 W user replaceable P-VIP lamp
Ceiling Mounting Capability	yes, with Auto Ceiling-Mount Correction
Power Consumption:	305 Watts (Operation), <1 Watts (Standby)
Power Supply	AC Input 100~240V auto-switching power supply
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 Composite Video (RCA) x 1 S-Video (Mini DIN) x 1 Component (3 RCA) x 1 HDMI (Video, Audio, HDCP) x 1 PC Audio (Stereo mini jack) x 1 USB (Type B) x 1 RS232 (Mini DIN) x 1
Bundled Accessories:	AC power cord VGA cable Composite video cable Remote control Battery for remote control Lens cap Carrying case User's guide (CD-ROM) Quick start guide Security card
Warranty	Acer projectors support a 2 year carry-in warranty and 1 year warranty for the lamp.

model	part number	price + VAT
H7530D		
H7530D DLP 1080p UK/EUR/SWI Power EMEA	EY.J9901.001	EUR 1199.00

H5350

**Target User**

- Kotikäyttäjät

Key Selling Points

- Captivating imagery
- Easy usability
- Diverse multimedia
- Rich functionality

StandardConfig

Display Technology	DLP™, Digital Light Processor
Native Resolution	Native 720p (1,280 x 720)
Compressed Resolution	Maximum UXGA (1,600 x 1,200)
Typical Colors	1.07 Billion Colors
Brightness (ANSI lumens)	2,000 ANSI Lumens (Standard), 1,600 ANSI Lumens (ECO)
Contrast Ratio	2000:1
Throw Ratio	58" @ 2m
Noise Level	32 dBA (Standard mode), 28 dBA (ECO mode)
Weight	2.3 kg (5.0 lbs)
Dimensions	267x 187 x 80 mm (10.5"x 7.4"x 3.1")
Computer Compatibility:	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards UXGA, SXGA, XGA, SVGA, VGA (resizing)
IR Remote Control	included
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio:	16:9 (Native), 4:3 Compatible
Horizontal Scan Rate:	31 ~ 100 kHz
Projection mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Vertical Scan Rate:	56 ~ 85 Hz
Projection Distance:	3.3' (1.0m) ~ 34.0' (10.4m)
Projection Screen Size (Diagonal):	26" (0.67m) ~ 300" (7.62m)
Digital Zoom	Yes, 2X
Keystone Correction:	+/-40 Degrees (Vertical)
Lamp Life	3,000 Hours (Standard), 4,000 Hours (ECO)
Lamp Type	180 W User Replaceable P-VIP Lamp
Ceiling Mounting Capability	yes
Power Consumption:	245 Watts (Operation), <8 Watts (Standby)
Power Supply	AC Input 100~240V auto-switching power supply
I/O Connectors	Analog RGB/Component Video (D - sub) x 1, Composite Video (RCA) x 1, S - Video (Mini DIN) x1, Component (3 RCA) x 1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 1, USB (Type B) x 1
Bundled Accessories:	AC power cord, VGA cable, Composite video cable, Remote control, Battery for remote control, Lens cap, User's guide (CD - ROM), Quick start guide, Security card
Warranty	Acer projectors support a 2 year carry-in warranty and 90 days warranty for the lamp.

model	part number	price	+ VAT
-------	-------------	-------	-------

H5360



Target User

- Kotikäyttäjät
- Ratkaisut ammattilaisille ja pientoimistoihin
- Pienet ja keskisuuret yritykset
- Suuret yritykset

Key Selling Points

- Brilliant 3D entertainment
- Perfect movie projection
- Immersive 3D visuals
- Easy-to-use design

StandardConfig

Display Technology	DLP™, Digital Light Processor
Native Resolution	Native 720p (1280 x 720)
Compressed Resolution	Maximum UXGA (1600 x 1200), 1080p (1920 x 1080)
Typical Colors	1.07 Billion Colors
Brightness (ANSI lumens)	2500 ANSI Lumens (Standard), 2000 ANSI Lumens (ECO)
Contrast Ratio	3200:1
Throw Ratio	58"@2m (1.55 ~ 1.70:1)
Noise Level	32 dBA (Standard mode), 27 dBA (ECO mode)
Weight	2.2 kg (4.9 lbs)
Dimensions	268 x 192 x 80 mm (10.6"x 7.6"x 3.1")
Computer Compatibility:	IBM PC and Compatibles, Apple Macintosh, iMac, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
IR Remote Control	included
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio:	16:9 (Native), 4:3 Compatible
Horizontal Scan Rate:	30k ~ 100k Hz
Projection mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Vertical Scan Rate:	50 ~ 85 Hz, 50 ~ 120 Hz (Available from Dec 2009)
Projection Distance:	3.3' (1.0m) ~ 33.8'(10.3m)
Projection Screen Size (Diagonal):	27"(67cm) ~ 300"(762cm)
Digital Zoom	Yes, 2X
Keystone Correction:	+/-40 Degrees (Vertical), Manual & Auto
Lamp Life	3000 Hours (Standard), 4000 Hours (ECO)
Lamp Type	200 W user replaceable P-VIP lamp
Ceiling Mounting Capability	Yes, with Auto ceiling-mount correction
Power Consumption:	224 Watts (Operation), <1 Watts (Standby)
Power Supply	AC Input 100~240V auto-switching power supply
I/O Connectors	Analog RGB/Component Video (D-sub) x 1 </p> Composite Video (RCA) x 1 </p> S-Video (Mini DIN) x 1 </p> Component (3 RCA) x 1 </p> HDMI (Video, Audio, HDCP) x 1 </p> PC Audio (Stereo mini jack) x 1 </p> RS232 (Mini DIN) x 1 </p>
Bundled Accessories:	AC power cord </p> VGA cable </p> Composite video cable </p> Remote control </p> Battery for remote control </p> Lens cap </p> Carrying case </p> User's guide (CD-ROM) </p> Quick start guide </p> Security card </p>
Warranty	Acer projectors support a 2 year carry-in warranty and 1 year warranty for the lamp.

model	part number	price + VAT
H5360 Brightness 2500, Lamp life 3000/4000, Native resolution 720p, Contrast ratio 3200:1, Throw ratio 58"@2m, Zoom, Audio, HDMI, Warranty 2YR C&R, Weight 2,2, EAN 4717276016098, Nvidia&DLP 3D	EY.K0701.013	EUR 619.00